



Documentation:

Ag++ Manual:

Georg Blaschke

Version 0.9

Contents

1	Introduction	4
2	Invocation	4
2.1	Concept	4
2.2	Options	4
2.2.1	--gen_config	5
2.2.2	--weave_only	5
2.2.3	--path	5
2.2.4	-c	5
2.2.5	-v --verbose [<arg>]	5
2.2.6	--aspect-header <arg>	5
2.2.7	--keep_woven	7
2.2.8	--c_compiler	7
2.2.9	--ac_compiler	7
2.2.10	--config_command	7
2.2.11	--config <arg>	7
2.2.12	--Xcompiler	7
2.2.13	--Xweaver	7
2.3	Generating dependency information	7
2.4	Examples	8

1 Introduction

The `ag++` program provides a more intuitive frontend to the AspectC++ weaver (`ac++`) in a GNU environment. The only preliminaries are a working installation of GNU C++ compiler, which also can run within a cygwin environment. It basically wraps the functionality of the aspect weaver and the c++ compiler into one single program.

2 Invocation

The usage of `ag++` is mainly influenced by the usage of the GNU `g++` compiler and the synopsis is like:

```
ag++ [options] [files...].
```

Let's say, you want to **compile** a single file (here: `main.cc`) with `g++`, you have to run

```
g++ -c main.cc
```

in order to generate an object file.

To **weave** and **compile** a single file you simply invoke

```
ag++ -c main.cc
```

the same way like you did before with `g++`.

2.1 Concept

As `ag++` is just a wrapper, it first generates the puma configuration file, then calls `ac++` and afterwards `g++`. The intermediate files generated by `ac++` are stored in the directory which is extracted from the `-o` option or in current directory. In some cases this may lead to a situation where the names of intermediate files interfere with each other.

2.2 Options

All available options are summed up in the options table (see table 1). The column labeled with *AC++* shows if the option is taken over from `ac++` by `ag++` ('X'), not supported by `ac++` ('-') or modified by `ag++` ('!'). All options which are taken over, are not described in this document. Consult the AC++ Compiler Manual instead. Options which are not listed in the option table are accounted as `g++` options. Some `g++` options can not be automatically handled correctly by

the options parser of `ag++`. So all `g++` options starting with `-p`, `-a`, `-d` and `-r` (e.g. `-pipe`, `-ansi`, `-dletters`, `-remap`) have to be written between `--Xcompiler` (see 2.2.12) and `--Xweaver` (see 2.2.13). If such options passed to `ag++` without using `--Xcompiler` they will be interpreted as `ag++/ac++` options ; e.g. `-pipe` will be interpreted as `-p "ipe"`.

2.2.1 `--gen_config`

Just create a parser configuration and quit afterwards. The argument of the `-o` option specifies the name of the file. In any other case (no `--gen_config` and/or no `-o` option) a configuration file with the name 'puma.config' will be generated in the directory where `ag++` was invoked.

2.2.2 `--weave_only`

Generate only woven source code files. With `-o` option and one file the generated output is named after the argument of the `-o` option.

2.2.3 `--path`

This options differs only slightly from the `--path` option of `ac++`. In `ac++` it is mandatory to specify a project path, whereby `ag++` the current working directory is used as project path by default. Especially for larger projects it is NOT wise to rely on the default project path, as weaving take a lot of time. See the AspectC++ Compiler Manual for a more detailed description of this option.

2.2.4 `-c`

Like the `-c` option of `g++`, this options effects the creation of object files of one or more source files.

2.2.5 `-v|--verbose [<arg>]`

Set the level of verbosity.

2.2.6 `--aspect-header <arg>`

This option differs from meaning in `ac++` only if dependencies are generated (see 2.3).

Option	AC++	Description
--gen_config	-	Only generate Puma configuration file
--weave_only	-	Weave only
-c	!	Compile only
--keep_woven	-	Keep woven source code files
--c_compiler <arg>	-	Path to C++ compiler
--ac_compiler <arg>	-	Path to AspectC++ compiler
--config_command <arg>	-	Specify command which prints information about compiler
--Xcompiler	-	In case of doubt account following options as g++ options.
--Xweaver	-	In case of doubt account following options as ac++ options.
-p --path <arg>	!	Defines a project directory
-d --dest <arg>	X	Specifies a target directory for saving
-v --verbose <arg>	!	Level of verbosity (0-9)
-o --output <arg>	X	Name of the output file
--include_files	X	Generate manipulated header files (short version -i is not supported)
-a --aspect_header <arg>	!	Name of aspect header file or 0
-r --repository <arg>	X	Name of the project repository
--expr <arg>	X	Pointcut expression to match in repository
--config <arg>	!	Parser configuration file
--no_line	X	Disable generation of #line directives
-k --keywords	X	Allow AspectC++ keywords in normal project files
--real-instances	X	Let ac++ perform a full template analysis
--problem...	X	Enable back-end compiler problem workaround
--no_problem...	X	Disable back-end compiler problem workaround
--warn...	X	Show a specific ac++ warning that is suppressed by default
--no_warn...	X	Suppress a specific ac++ warning
-I <arg>	X	Include file search path
-D <name>[=<value>]	X	Macro definitions
-U <name>	X	Undefine a macro
--include <arg>	X	Forced include

Table 1: ag++ Compiler Option Summary

2.2.7 --keep_woven

Don't remove intermediate woven files.

2.2.8 --c_compiler

Specify path to GNU C++ compiler` The default is g++ .

2.2.9 --ac_compiler

Specify path to AspectC++ compiler` By default ag++ assumes, that the ac++ executable is located in the same directory like itself.

2.2.10 --config_command

Specify the command which prints information about the compiler. This information is necessary for generating the parser (puma) configuration file. The default value is "`<compiler> <compiler options> -E -dM -v -x c++ <an empty file>`".

2.2.11 --config <arg>

Path to a puma configuration file. If this option is available the configuration file will not be generated automatically.

2.2.12 --Xcompiler

ac++ and ag++ options that might interfere with g++ options are not recognized after using --Xcompiler in the argument list of an ag++ invocation.

2.2.13 --Xweaver

Enable the recognition of those ac++ and ag++ options which previously have been disabled by the usage of --Xcompiler .

2.3 Generating dependency information

To produce dependency files just pass the `-M` or `-MM` (consult the GNU C++ Compiler Manual) to ag++ . Dependency files generated by ag++ are slightly different from dependency files created by g++, as they contain dependencies to aspect header files. If the `--aspect-header` option is provided, only the header

file specified as option argument is considered when building the dependency file; otherwise the dependency file will contain all aspect header files within the whole project path .

2.4 Examples

- `ag++ --help`
Displays all options with a short description.
- `ag++ -o test Test.cc main.cc`
Weave, compile and link the source files `Test.cc` and `main.cc`. The created executable will be named 'test'.
- `ag++ --gen_config`
Create a puma configuration file named `puma.config` within the current working directory.
- `ag++ --gen_config -o my.config`
Create a puma configuration file named `my.config`.
- `ag++ --path src --include_files --dest gen/includes`
Generate modified include files out of all include files found below `src` directory and store them under 'gen/includes'.
- `ag++ -M -MFmain.dep main.cc`
Generate dependency file `main.dep` from source file `main.cc` .
- `ag++ -p ../aspects -p . --Xcompiler`
This string could be used to substitute `g++` in a simple make environment.